

PRS MODIFIED BASE SHEET

Modified Base Sheet

Product Description

- ▶ PRS MODIFIED BASE is an SBS polymer modified bitumen sheet designed for use as a hot-mopped or PERMASTIC Cold Adhesive applied base sheet and/or ply sheet. PRS MODIFIED BASE is a unique fiberglass reinforced, modified bitumen material that lays flat and provides a superior base for asphaltic based membrane systems. PRS MODIFIED BASE may be used as a roofing and flashing base ply.

Uses

- ▶ PRS MODIFIED BASE sheet is used as a nailed base sheet or easily installed in hot asphalt applications.

Special Characteristics

- ▶ Superior nail pull-through resistance
- ▶ Combined strength of fiberglass mat and SBS modified asphalt
- ▶ Puncture resistant
- ▶ UL Classified Base/Ply sheet
- ▶ FM Approved
- ▶ ASTM D 4601, Type II

Product Information

Length	97 ft 6 in	29.7 m
Width	39 3/8 in	1 m
Coverage	300 sq ft	27.9 m ²
Weight	79 lbs/roll	35.9 kg

MSDS Available on Request at (800) 727-9872 or at www.derbigum.com.

Product Description

Rolls shall be stored on end on raised platforms and protected from the weather.



* This document cancels and replaces any other document published previously. All values shown are nominal and subject to normal manufacturing tolerances.



4800 Blue Parkway
Kansas City, MO 64130
Phone: 800.727.9872 / Fax: 816.924.1542
E-mail: info@derbigum.com Web: www.derbigum.com

WWW.DERBIGUM.COM