

PRS ASPHALT ROOF PRIMER

Asphaltic Based Primer

Product Description

- ▶ PRS PRIMER is a asphaltic based primer that meets ASTM D-41 standards and is designed for use with asphaltic based roofing, waterproofing and coatings.

Uses

- ▶ PRS PRIMER is a general priming coat used to improve adhesion and provide maximum bond to concrete, metal, porous insulation surfaces and for recover applications.

All surfaces to be primed must be clean, dry and free of dirt and debris.

Application

Rate : 1 - 2 gal/sq.

Note: Coverage may vary with absorption rate.

Tools : Apply with a roller, brush or spray to distribute evenly
Due to possible settling of the primer, stirring may be required before use.

For exact application instructions, refer to the DERBIGUM Specification & Detail Manual

Product Information

| | |
|-------------------------|------------------------------|
| Weight : | 7.2 lbs/gallon (0.86 kg/L) |
| VOC: | 500 grams/L (4.0 lbs/gallon) |
| Non-volatile Contents : | 50% (Solids) |
| Flash Point : | >100°F (ASTM D-93) |

MSDS Available on Request at (800) 727-9872 or at www.derbigum.com.

Packaging & Storage

PRS PRIMER is available in the following container sizes :
5 gallon pails (18.9 L); 36 pails/pallet - Approx. 1,800 lbs (820 kg) / pallet
55 gallon drums (208 L); 4 drums/pallet - Approx. 2,250 lbs (1,022 kg) / pallet

Florida State
Wide Approval



* This document cancels and replaces any other document published previously.
All values shown are nominal and subject to normal manufacturing tolerances.



DERBIGUM®
MAKING BUILDINGS SMART

4800 Blue Parkway
Kansas City, MO 64130
Phone: 800.727.9872 / Fax: 816.924.1542
E-mail: info@derbigum.com Web: www.derbigum.com

WWW.DERBIGUM.COM