

DERBICOLOR® XPS

Granule surfaced APP modified bitumen triple reinforced roof membrane

Product Description

- ▶ DERBICOLOR XPS is a premium 4.5 mm (180 mil) granule surfaced, APP modified bitumen waterproofing membrane. DERBICOLOR XPS is **triple reinforced** with a glass mat along with a glass and polyester composite mat to provide superior tensile properties, and puncture resistance. DERBICOLOR XPS may be used as roofing and flashing membrane, and as walkway material.
- ▶ May be applied in PERMASTIC Cold Adhesive or heat welded.



Technical Characteristics

	Units	ASTM Requirements ATSM D 6223-02	DERBICOLOR XPS Results*
Tensile Strength	0°F	lbf/in.	Machine direction / Cross Direction 260/240
	77°F	lbf/in.	120/120
Elongation	0°F	%	5.00/5.00
	77°F	%	5.00/5.00
Tear Resistance	77°F	lbf	200/200
Cold Flex		°C	-20
M.I.T	< 5 % Blisters		

Special Characteristics

DERBICOLOR XPS is a UV resistant APP Modified Bitumen Membrane with granules added for color options, and has a proven durability for over 25 years.

Product Information*

	Test Method	Values	Units	Values	Units
Thickness	ASTM D 5147	180	mils	4.5	mm
Length	ASTM D 5147	33.4	ft	10.2	m
Width	ASTM D 5147	39.4	in	1.00	m
Net Coverage		100	sq ft	9.29	m ²

MSDS Available on Request at (800) 727-9872 or at www.derbigum.com.

Storage

Rolls shall be stored on end on raised platforms and protected from the weather.



WWW.DERBIGUM.COM



DERBIGUM®
MAKING BUILDINGS SMART

4800 Blue Parkway
Kansas City, MO 64130
Phone: 800.727.9872 / Fax: 816.924.1542
E-mail: info@derbigum.com Web: www.derbigum.com