



NOTES:

1. WHERE THE DECK IS SUPPORTED BY AND FASTENED TO THE CONCRETE DECK WALL, VERTICAL WOOD NAILERS ARE REQUIRED AND SHOULD BE SECURED TO THE WALL WITH SUITABLE FASTENERS.
2. PERFORMANCE ROOF SYSTEMS DETAIL DRAWINGS: REFER TO PERFORMANCE ROOF SYSTEMS AND OTHER RELATED PUBLISHED DOCUMENTATION, PRODUCT DATA SHEETS (PDS) AND SAFETY DATA SHEETS (SDS) FOR ADDITIONAL INFORMATION. ALL DETAIL DRAWINGS AND RELATED INSTALLATION GUIDELINES ARE PROVIDED BY PERFORMANCE ROOF SYSTEMS FOR THE SOLE PURPOSE OF ISSUING A PERFORMANCE ROOF SYSTEMS WARRANTY. ACCORDINGLY, THE DETAIL DRAWINGS ARE NOT OFFERED, AND SHOULD NOT BE CONSIDERED, AS A SUBSTITUTE FOR PROFESSIONAL DESIGN SERVICES.
3. PRIMER: WHERE NOT SHOWN OR INDICATED ON DETAIL DRAWINGS, REFER TO MATERIAL PRODUCT DATA SHEETS FOR PRIMER APPLICATION REQUIREMENTS
4. PERFORMANCE ROOF SYSTEMS RECOMMENDS 8 INCH VERTICAL FLASHING HEIGHTS. FLASHING DETAILS SHOWN INCLUDE MINIMUM DIMENSIONS TO MEET WARRANTY REQUIREMENTS. CONTACT PERFORMANCE ROOF SYSTEMS FOR ADDITIONAL REQUIREMENTS.



**PERFORMANCE
ROOF SYSTEMS**
A SOPREMA® GROUP COMPANY
4800 DR. MARTIN LUTHER KING JR. BLVD
KANSAS CITY, MO 64130
816.921.0221
WWW.PERFORMANCEROOFSYSTEMS.US

P-3L WALL/SURFACE MOUNTED COUNTERFLASHING

DRW
JS

CHK
LC

ISSUED
12/14/15
REV
1.1

DETAIL NO.
P-3L SD
NOT TO SCALE