

# PRS GLASS BASE<sup>®</sup>

Fiberglass Base Sheet

## ADVANTAGES

- ▶ High quality base or ply sheet constructed from fiberglass mat coated with oxidized asphalt
- ▶ Product is intended to be used over lightweight insulating fill decks, gypsum or other substrates where lateral venting is required.
- ▶ Adds inter-ply adhesion between base ply and the membrane
- ▶ Excellent strength for nail-holding ability
- ▶ Manufactured with ply lines for easy installation
- ▶ Meets or exceeds ASTM D4601 Type II specifications
- ▶ Product carries an Underwriters Laboratories G2 classification
- ▶ Made from inorganic material that resists rotting
- ▶ Can be applied using hot asphalt or mechanical fasteners



## TECHNICAL CHARACTERISTICS

CHARACTERISTIC	TESTED	ASTM Requirements Test Methods D4601 Type II		PRS Glass Base Results*		UNITS
		MACHINE DIRECTION	CROSS DIRECTION	MACHINE DIRECTION	CROSS DIRECTION	
<b>Tensile Strength</b>	73°F	50	50	<b>63</b>	<b>63</b>	lb/in

\* All values shown are nominal and subject to normal manufacturing tolerances.

## PRODUCT INFORMATION

CHARACTERISTIC	U.S. CUSTOMARY	METRIC
<b>Length</b>	108 ft	32.9 m
<b>Width</b>	36 in	0.9 m
<b>Weight</b>	78.5 lb	35.6 kg
<b>Net Coverage</b>	291.7 sq ft	27 sq m

## PACKAGING & STORAGE

Packaged 20 rolls per pallet. Rolls should be stored on end, on raised platforms protected from the weather



SDS available  
on request:  
(800) 727-9872  
www.derbigum.us

