

# PERFLASH®

Modified Bitumen Flashing Cement

## ADVANTAGES

- ▶ Premium grade modified asphalt flashing formulated for adhering Derbigum polymer modified asphalt flashing membranes to vertical surfaces
- ▶ Excellent adhesion and enhanced waterproofing due to over 85% solids content.
- ▶ Product can also be used for filling pitch pans, setting roof drain leads and metal flashing components.
- ▶ VOC compliant —meets stringent EPA air quality standards with low fumes
- ▶ No kettles, dangerous chemicals

## APPLICATION

**RATE:** 7.5 gallons per 100 sq ft (31 sq m) at 1/8 inch  
 Note: Coverage may vary with absorption

**TOOLS:** A trowel or a gloved hand to distribute evenly

*For exact application instructions, refer to the Derbigum Specification & Detail Manual*



## PRODUCT INFORMATION

CHARACTERISTIC	U.S. CUSTOMARY	METRIC
<b>Weight</b>	9.1 lb/gal	1.09 kg/L
<b>VOC</b>	1.3 lb/gal	165 g/L
<b>Flash Point</b>	>120 °F	>48.8 °C

<b>Non-Volatile Contents</b>	86% solids
<b>Solids Volume</b>	>50%

## PACKAGING & STORAGE

PERFLASH is available in the following containers sizes:

30 ounce cartridge (.88 L)

3 gallon pail (11.4 L)

5 gallon pail (18.9 L)

Approximate shelf life is 12 months with proper storage.

