

PERMASTIC®

Unique Asphaltic Bases, Cold Process Adhesive

ADVANTAGES

- ▶ Cold applied adhesive for use with modified bitumen membranes, base sheets, and other cold process roofing systems
- ▶ Excellent adhesion and enhanced waterproofing due to over 80% solids content
- ▶ Thixotropic properties of the RubberLux® additives improve stability
- ▶ Improved productivity which minimizes open roofs
- ▶ Available in environmentally friendly reusable pails, drums and tanks
- ▶ No kettles, dangerous chemicals and low VOC emissions provides a safer work environment
- ▶ Meets the requirements of ASTM D 3019, Type III, Grade 2

APPLICATION

RATE: 2.0 gallons per 100 sq ft (90.81 sq m)

TOOLS: A notched squeegee or spray apparatus to distribute cold process adhesives.
A 20 lb steel roller to roll all side and ends laps that will be heat welded.

For exact application instructions, refer to the Derbigum Specification & Detail Manual



PRODUCT INFORMATION

CHARACTERISTIC	U.S. CUSTOMARY	METRIC
Weight	9 lb/gal	1.07 kg/L
VOC	1.6 lb/gal	200 g/L
Flash Point	>105 °F	>40.5 °C

Non-Volatile Contents	78-83% solids
------------------------------	---------------

PACKAGING & STORAGE

PERMASTIC is available in the following containers sizes:

- 5 gallon pail (18.9 L) (4.7 gal per volume)
- 55 gallon drum (208.2 L) (53.3 gal per volume)
- 350 gallon reusable tank (1,323 L)

Store in a well-ventilated area far away from any heat source.



SDS available
on request:
(800) 727-9872
www.derbigum.us

