

PLASTIC ROOF CEMENT

Long-Lasting General Purpose Sealant

ADVANTAGES

- ▶ Made of refined asphalt, solvents and non-asbestos fillers to be used as to temporarily patch for cracks, breaks in roof surfaces, daily water cutoffs or roofing metal embedment
- ▶ Can be used for flashing around skylights, chimneys, vents, and gutters.
- ▶ Heavy bodied consistency for easy trowel application
- ▶ Meets or exceeds ASTM D4586 Type 1 standards

APPLICATION

RATE: Approximately ¼ inch thick

TOOLS: Apply with a trowel, putty knife or gloved hand
All surfaces to be primed must be clean, dry and free of dirt and debris.

For small hairline cracks fill the crack space and feather down at edges.

For larger cracks and voids it may be necessary to use a fabric membrane with the Plastic Roof Cement. Apply cement approximately ¼ inch thick to area, then embed fabric membrane directly into cement. Apply another coat of cement over the area and feather down at the edges.

For exact application instructions, refer to the Derbigum Specification & Detail Manual



PRODUCT INFORMATION

CHARACTERISTIC	U.S. CUSTOMARY	METRIC
Weight	8.9 lb/gal	0.86 kg/L
VOC	2.5 lb/gal	300 g/L
Flash Point	>100 °F	>37.7 °C
Non-Volatile Contents	70 % minimum	

PACKAGING & STORAGE

Roof Cement is available in the following sizes:

PRODUCT	# PER PALLET	PALLET WEIGHT
5 Gallon Pail	42	2,150 lb
55 Gallon Drum	4	2,250 lb

SDS available
on request:
(800) 727-9872
www.derbigum.us

