

# PRS VENTED BASE®

Fiberglass Venting Base Sheet

## ADVANTAGES

- ▶ Heavyweight fiberglass venting base sheet constructed with fiberglass mat coated with asphalt.
- ▶ Product is intended to be used over lightweight insulating fill decks, gypsum or other substrates where lateral venting is required.
- ▶ Meets or exceeds ASTM D4897 Type II specifications
- ▶ Product carries an Underwriters Laboratories G2 classification
- ▶ Made from inorganic material that resists rotting
- ▶ Porosity of the felt allows for better asphalt penetration
- ▶ Can be applied using hot asphalt, PERMASTIC cold adhesive or mechanical fasteners



## TECHNICAL CHARACTERISTICS

CHARACTERISTIC	TESTED	ASTM Requirements Test Methods D4897 Type II		PRS Vented Base Results*		UNITS
		MACHINE DIRECTION	CROSS DIRECTION	MACHINE DIRECTION	CROSS DIRECTION	
<b>Tensile Strength</b>	73°F	50	50	<b>67</b>	<b>61</b>	lb/in

\* All values shown are nominal and subject to normal manufacturing tolerances.

## PRODUCT INFORMATION

CHARACTERISTIC	U.S. CUSTOMARY	METRIC
<b>Length</b>	32 ft 11 in	10 m
<b>Width</b>	39 3/8 in	1.0 m
<b>Weight</b>	87 lb	39.4 kg
<b>Net Coverage</b>	97.5 sq ft	9 sq m

## PACKAGING & STORAGE

Packaged 20 rolls per pallet. Rolls should be stored on end, on raised platforms protected from the weather



SDS available  
on request:  
(800) 727-9872  
www.derbigum.us